



KORO® BY IMANTS

TopDrain 1000

Complete one-pass surface drainage system. The TopDrain 1000 is a unique multifunctional machine that trenches, removes spoil, injects sand and re-compacts all in one operation. Designed for sportsfields and golf course fairways, the TopDrain benefits include; material and labour savings, faster processing times and less surface contamination than conventional methods. The sand grid created by the TopDrain is meant to compliment the existing drainage system.

Specification

| | |
|---------------------------------------|--|
| Working width | 1.00m |
| Overall width | 2.24m |
| Machine height (machine on legs) | 2.52m * rear wheels lowered |
| Height of elevator (blades on ground) | 1.70m |
| Height of hopper (blades on ground) | 1.85m |
| Machine length | 4.99m |
| Working depth | 260mm (maximum) |
| Weight (approx) | 2,500kgs (unladen) |
| Number of cutting discs | 2 |
| Spacing of discs | 1.00m |
| Thickness of digging blades | 4cms |
| Power requirement | 55hp – 85hp maximum |
| Tractor requirements | 540 pto / 6 spline pto 6 hyd valves – female fittings on tractor required |
| Operating speed | 0 – 3 kph |
| Tractor requirements | 540 pto. 2 x double, 1 x single spool, 12v plug |
| Options | Road lights |

