



RAYCAM™

SPEEDRESSER™ 18H

The RAYCAM™ SPEEDRESSER™ 18H is a bulk drop-spreader designed to handle all top dressing materials. The 4 flotation tyres on pivoting axle minimise the risk of turf damage & compaction. Ideal for golf courses & sports fields use, both with private clubs, local authorities and contractors. The SPEEDRESSER™ 18H requires a tractor of at least 30hp, and is driven hydraulically from the tractor via an agitator and twin rollers. The high work rate enables the spreading of dressings up to depths of 2mm - 75mm in one pass.

Specification	18H	18HG with extension hopper
Spreading width	1.80m	1.80m
Overall width	2.10m	2.10m
Body Length	3.00m with drawbar - 2.00m without	
Hopper Capacity	2.25m ³	3.25m ³
Loading height	1.4m	1.75m
Gross weight	4,000kg	5,500kg
Weight (unladen)	960kg	1,050kg
Tractor requirement	30hp +. Spool valve. Pick up hitch/drawbar	50hp +. Spool valve. Pick up hitch/drawbar
Tyres	4 x Ultra Trac 26.5 x 14 x 12	
Operating speed	Up to 12mph (18kph)	



RAYCAM™

SPEEDRESSER™ 24H

The RAYCAM™ SPEEDRESSER™ 24H is a 2.4m wide drop-spreader designed to handle all top dressing material. The 4 flotation tyres minimise the risk of turf damage & compaction. Ideal for golf courses & sports fields use, both with private clubs, local authorities and contractors. The SPEEDRESSER™ 24H requires a tractor of at least 75hp, and is PTO driven, via a heavy-duty transmission to an agitator and twin rollers. The twin rollers are now hydraulically adjustable against a pre-set stop to alter spreading rate applications. The high work rate enables the spreading of top dressings up to depths of 2mm - 75mm in one pass.

Specification

Spreading width	2.40m
Overall width	2.65m
Body Length	2.30m
Hopper Capacity	5.75m ³
Loading height	2.00m
Gross weight	9,250kg
Weight (unladen)	2,250kgs
Tractor requirement	75hp + Pick up hitch /drawbar & spool valve
Tyres	4 x Flotation tyres - 15.5 x 14ply
Operating speed	Up to 12mph (18kph)

