

KORO® BY IMANTS

TopDrain 1000

Complete one-pass surface drainage system. The TopDrain 1000 is a unique multifunctional machine that trenches, removes spoil, injects sand and re-compacts all in one operation. Designed for sportsfields and golf course fairways, the TopDrain benefits include; material and labour savings, faster processing times and less surface contamination than conventional methods. The sand grid created by the TopDrain is meant to compliment the existing drainage system.

Specification

Working width	1.00m
Overall width	2.24m
Machine height (machine on legs)	2.52m * rear wheels lowered
Height of elevator (blades on ground)	1.70m
Height of hopper (blades on ground)	1.85m
Machine length	4.99m
Working depth	260mm (maximum)
Weight (approx)	2,500kgs (unladen)
Number of cutting discs	2
Spacing of discs	1.00m
Thickness of digging blades	4cms
Power requirement	55hp – 85hp maximum
Tractor requirements	540 pto / 6 spline pto 6 hyd valves – female fittings on tractor required
Operating speed	0 – 3 kph
Tractor requirements	540 pto. 2 x double, 1 x single spool, 12v plug
Options	Road lights









KORO® BY IMANTS

TopDrain 1500

The TopDrain 1500 is a unique multifunctional machine that trenches, removes spoil, injects sand and re-compacts all in one operation. Designed for sportsfields and golf course fairways, the TopDrain benefits include; material and labour savings, faster processing times and less surface contamination than conventional methods. The sand grid created by the TopDrain complements existing drainage systems.

Specification

Working width / Overall width	1.50m / 2.75cms
Working depth	15 - 225mm
Number of cutting blades	3
Spacing of blades	50cm
Thickness of blades	40mm
Weight (approx)	3300kg (unladen)
Power requirement	95hp Creep gear
Tractor requirements	540 pto. 2 x double, 1 x single spool, 12v plug
Operating speed	0 - 1.8mph (0 - 3kph)
Options	Extended side conveyor. Hopper vibrator



