OFFICIAL VGR DISTRIBUTOR
campeyturfcare.com



VGR

TopChanger XP

The TopChanger XP is an aeration machine that works on the basis of water and high pressure. Water is used under high pressure to blow holes in the soil. Water aeration opens up possibilities for injecting sand, with soil-improving products if desired, into the soil.

The TopChanger XP performs all the operations necessary to treat your soil efficiently and sustainably in a single pass. And all this with minimal disruption to players.

Specification

Machine dry weight	700 kg
Horsepower requirement minimum	45 hp
PTO speed	540 / 540E rpm
Hopper capacity	0.25 m^2
Working speed	0.3 – 0.8 km/h
Injection pressure	200 – 260 bar
Inlet pressure required	2 – 8 bar
Working width	1.6 m
Hydraulic capacity during operation	Minimum 21 L/min



The Topchanger XP uses a heavy duty PTO driven water pump to pressurise the water between 200-260 bars of pressure controlled by the operator on the touchscreen control panel. The pressurised water is then pumped directly into 2 injection valves containing 10 nozzles per valve, the injection valves work independently allowing the Topchanger to follow any contours and undulations in the playing surface.

Water aeration: Can be used as a conventional aeration tool using water alone, depths of up to 400mm have been observed.

Sand injection: the machine can handle wet sands eradicating the need to buy expensive kiln dried sands. Injecting sand into the profile helps to dilute thatch and organic matter. It also improves drainage and infiltration while firming up the playing surface.

Campey supply market leading, innovative turf care machinery worldwide, we're continually researching new techniques and refining existing practices to help turf care professionals achieve perfection.

Call +44 (0)1260 224568, email info@campeyturfcare.com or **visit www.campeyturfcare.com**

CampeyTurfCare CampeySportsTurfMachinery CampeyMachinery CampeyTurfCare